

How To Install RT & Battery Assembly Cover

To install the Radio Transceiver (RT) and Battery Assembly cover and protect your RT and battery assembly from water ingress, follow the steps outlined below. This document applies to the CCAC-RTVMNT-COV only. If you have any questions or trouble performing this procedure, call CoachComm's Customer Support at 1.800.749.2761.

Installation Steps:

1. Take note of where your RT's whip antenna and connector cap are currently installed (antenna should be in the port labeled "R").
2. Remove the whip antenna and connector cap. Set them aside.
3. Install two of the provided rubber gaskets onto the RT's two antenna connectors.
4. Install the cover onto the RT by sliding it over the device from top to bottom. Make sure that the cover's logo is facing forward (same as the RT's logo) and that the ports on the bottom of the RT are accessible.
5. Push both antenna connectors through the holes in the cover.
6. Install two of the provided rubber gaskets onto the RT's two antenna connectors over the cover; then, reinstall the antenna and connector cap in their original locations.
7. If necessary, remount the RT and Battery Assembly on the tripod.

Note: CoachComm recommends to remove the RT cover from the RT and allow it to dry completely after a game where the RT cover gets wet.

Whip Antenna

Connector Cap

Rubber Gaskets

RT Cover

Rubber Gaskets

RT with Battery Assembly